

Quick Guide

Arterial Pressure Variation

What is arterial pressure variation?

Positive pressure ventilation causes blood pressure changes in the chest cavity: inspiratory phase increases the pressure and expiratory phase decreases it. The magnitude of these changes is dependent on the fluid status of the patient. In hypovolemic patients these swings are higher in amplitude compared to normovolemic or hypervolemic patients. This is a well known phenomenon.

The arterial pressure variation algorithm looks for respiratory changes in the arterial blood pressure. It only uses the arterial blood pressure analysis and does not use any other parameter to recognize the respiratory cycle.

Arterial pressure variation can be used to assess fluid responsiveness continuously and without extra procedures¹.

Arterial blood pressure variation in GE patient monitoring


Systolic pressure variation (SPV) and pulse pressure variation (dPP) reflect respiratory changes in arterial pressure during positive pressure ventilation. (1, 2, 3)

SPV and dPP are calculated from the invasive arterial blood pressure using the following equations:


$$\text{SPV [mmHg]} = \text{SBPmax} - \text{SBPmin}$$

$$\text{dPP [\%]} = (\text{PPmax} - \text{PPmin}) / [(\text{PPmax} + \text{PPmin}) / 2] * 100$$

SBPmax and SBPmin represent the maximum and minimum values of a systolic blood pressure over the measurement period, respectively.



PPmax and PPmin represent the maximum and minimum pulse pressures.



Values of SPV are represented in mmHg whereas dPP is a percentage. Both numbers are computed once every five seconds. The measurement is continuous and trended in the GE patient monitor. When the monitoring is started it requires two respiratory cycles before the values are shown on the screen.



The arterial pressure variation algorithm analyzes the acquired invasive arterial blood pressure signal and, therefore, it does not require any further equipment besides the invasive blood pressure measurement kit.


Why monitor SPV/dPP?

One of the most common questions regarding hemodynamics has to do with the patient's fluid responsiveness: Will the patient's stroke volume and cardiac output improve with fluid resuscitation?

In hypovolemic conditions respiratory variations in stroke volume are higher than normal¹. However, being responsive to fluid therapy does not mean that the patient really needs fluid.

Monitoring arterial pressure variation, i.e. SPV/dPP, helps to answer the question of fluid responsiveness and can be used to guide fluid expansion therapy⁴. SPV/dPP parameters cannot, however, indicate what type of fluid is the most suitable for the therapy.

The Frank-Starling curve describes the relation between stroke volume and preload. The steeply rising section of the curve represents the area where the patient is responsive to fluid therapy. It means that a small increase in preload results in a large increase in stroke volume and cardiac output. On the other hand, when moving to the flat area of the curve, the change in preload hardly makes a difference in stroke volume.



Threshold value suggested in the literature

High values of delta pressures indicate responsiveness to fluid therapy. The values shown in literature for dPP to indicate fluid responsiveness range from 10 to 15%^{1, 5}. If the value is over the limit, it is suggested that the patient is responsive to fluid loading.

This range holds true when the limitations of the parameter have been ruled out.

Limitations

There are a few limitations with the clinical use of dPP and SPV. Firstly, they are only reliable when the patient is mechanically ventilated.

Secondly, dPP and SPV are reliable only with patients without cardiac arrhythmias. The algorithm uses the monitored ECG signal for cardiac arrhythmia recognition.

Since SPV and dPP values are calculated from the invasive arterial blood pressure waveform, they are reliable only if the readings of the invasive blood pressure are reliable. The invasive blood pressure transducer needs to be at the mid-heart level, adequately zeroed, and there should not be air in the transducer dome or in the catheter line.

The GE patient monitor analyzes the invasive arterial blood pressure signal from which it calculates the arterial pressure variation parameters. The analysis is done to the invasive blood pressure channel, which is labeled "Art" in the patient monitor.

Availability of the arterial pressure variation monitoring is subject to the software version of the GE patient monitor. In the S/5 product line L-ANE07(A) or L-ICU07(A) or newer is required.

References

1. Michard, Changes in Arterial Pressure during Mechanical Ventilation. *Anesthesiology* **(103)** 419-28 (2005).
2. Perel, A., et. al. Systolic blood pressure variation is a sensitive indicator of hypovolemia in ventilated dogs subjected to graded hemorrhage. *Anesthesiology* **(67)**, 498-502 (1987).
3. Michard, F., et. al. Clinical use of respiratory changes in arterial pulse pressure to monitor the hemodynamic effects of PEEP. *Am J Respir Crit Care Med*, **(159)**, 935-9 (1999).
4. Preisman, S., et. al. Predicting fluid responsiveness in patients undergoing cardiac surgery: functional haemodynamic parameters including the Respiratory Systolic Variation Test and static preload indicators. *Br J Anaesth* (2005).
5. Deflandre, E., et. al. Delta down compared with delta pulse pressure as an indicator of volaemia during intracranial surgery. *Br J Anaesth*, **100**, 245-250 (2008).

© 2010 General Electric Company – All rights reserved.

GE and GE Monogram are trademarks of General Electric Company.

GE Healthcare reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your GE Healthcare representative for the most current information.

GE Healthcare Finland Oy, a General Electric company, doing business as GE Healthcare.

GE Healthcare, a division of General Electric Company.

CAUTION: U.S. Federal law restricts this device to sale by or on the order of a licensed medical practitioner.

Consult the monitor User's Guide for detailed instructions.

About GE Healthcare:

GE Healthcare provides transformational medical technologies and services that are shaping a new age of patient care. Our broad expertise in medical imaging and information technologies, medical diagnostics, patient monitoring systems, drug discovery, biopharmaceutical manufacturing technologies, performance improvement and performance solutions services help our customers to deliver better care to more people around the world at a lower cost. In addition, we partner with healthcare leaders, striving to leverage the global policy change necessary to implement a successful shift to sustainable healthcare systems.

Our “healthymagination” vision for the future invites the world to join us on our journey as we continuously develop innovations focused on reducing costs, increasing access and improving quality around the world. Headquartered in the United Kingdom, GE Healthcare is a unit of General Electric Company (NYSE: GE). Worldwide, GE Healthcare employees are committed to serving healthcare professionals and their patients in more than 100 countries. For more information about GE Healthcare, visit our website at www.gehealthcare.com.

GE Healthcare
8200 West Tower Avenue
Milwaukee, WI 53223
U.S.A.

www.gehealthcare.com

GE Healthcare Finland Oy
Kuortaneenkatu 2
00510 Helsinki
Finland

GE Healthcare
3/F Building # 1,
GE Technology Park
1 Hua Tuo Road
Shanghai 201203

China



imagination at work